

EMBLEM Solvent POS Film Plus FR

EMBLEM Solvent POS Film Plus FR

Matchcode:	SOPFPFR
Material:	rigid PVC
Finish:	semimatt
Colour:	white
Thickness:	300 µm ± 7%
Tensile impact strength (DIN EN ISO 8256)	≥ 450 kJ/m ²
VICAT-Softening (DIN EN ISO 306)	73 °C ± 2
Cold break temperature (DIN EN 1876-2)	-30 °C
Width of rolls:	105 cm / 54"
Length of rolls:	25 m
Compatible inks:	
Eco solvent:	yes
Solvent:	yes
UV-curable:	yes
Latex:	no
Flame retardant:	DIN 4102-B1 NF P 92-512-M1

Description:

EMBLEM SOPFPFR is a white rigid PVC film to print with UV, eco-solvent and solvent inks. The print is water-proof with brilliant colours on the semimatt surface.

This special film is for indoor and outdoor application at POS like poster, banner, fair constructionsroll and shop-decoration.

Advise for workmanship:

The drying of the printed medium is highly dependent on the inks used and the colour saturation. When printing film in a roll-to-roll process, the printed strip should unrolled and laid flat as soon as possible until final drying. Solvent residues due to insufficient drying times can damage the PVC structure and lead to blocking during transport in rolled-up form. During lamination such residues can negatively impact flatness, the shrinkage behaviour and the anchorage of the laminate on the printed film.

We recommend to protect the printed surface if it is subject to abrasion, sweat or other mechanical influences. In this case we recommend to protect the image with laminating film.

To avoid fingerprints the use of cotton-gloves is advisable

Small print

Because of the great number of potential influences at object time and appliance of the above-mentioned materials, on which we have no bearing, test prints have to be effected by the user himself. A legally binding warranty can not be deduced from our specifications. Every liability and warranty that goes beyond the warranty of the product amounting to the product's value as well as entitlements to damages are excluded.